




Modern surface mounted luminaire for LED light sources.

TECHNICAL DATA	Mounting: directly on the ceiling Body: powder-painted steel sheet Colour: white
ELECTRICAL DATA	Diffuser: opal plexiglass (PLX) Power supply efficiency: >89% Power: 220-240V 50/60Hz Includes light source: yes
OPTICAL DATA	Type of equipment: STANDARD, DALI, EM 3h Electrical connection: max 3x2,5 mm ² wire Light distribution: rotationally-symmetric Way of lighting: direct
ADDITIONAL INFO	Operating temperature range: 0° C ... +35° C Lifetime (L70B50): 50 000 h
GENERAL DATA	Glow Wire Test: Warranty: 3 years Application: pathways, conference rooms



Code	Replacement of conventional technology [W]	Power LED [W]	Luminaire power [W]	Lumen LED [lm]	Lumen luminaire [lm]	Efficacy [lm/W]	Colour temperature [K]	CRI/Ra
Type of equipment: STANDARD								
300061.00062	3x14W (57W)	22	24	3150	2600	108	3000	≥80
300061.00063	3x14W (57W)	22	24	3150	2600	108	4000	≥80
300061.00064	4x14/18W (76W/96W)	33	37	4500	3700	100	3000	≥80
300061.00065	4x14/18W (76W/96W)	33	37	4500	3700	100	4000	≥80
Type of equipment: DALI								
300061.00071	3x14W (57W)	22	24	3150	2600	108	3000	≥80
300061.00072	3x14W (57W)	22	24	3150	2600	108	4000	≥80
300061.00073	4x14/18W (76W/96W)	33	37	4500	3700	100	3000	≥80
300061.00074	4x14/18W (76W/96W)	33	37	4500	3700	100	4000	≥80
Type of equipment: EM 3h								
300061.00075B	3x14W (57W)	22	29	3150	2600	90	3000	≥80
300061.00076B	3x14W (57W)	22	29	3150	2600	90	4000	≥80
300061.00077B	4x14/18W (76W/96W)	33	39	4500	3700	95	3000	≥80
300061.00078B	4x14/18W (76W/96W)	33	39	4500	3700	95	4000	≥80

Code	Dimensions [mm] L W H	Mounting dimensions [mm] L W	Pallet quantity	Quantity in package	Net weight [kg]
Type of equipment: STANDARD					
300061.00062	626 626 70	375 435	50	1	5.7
300061.00063	626 626 70	375 435	50	1	5.7
300061.00064	626 626 70	375 435	50	1	5.7
300061.00065	626 626 70	375 435	50	1	5.7
Type of equipment: DALI					
300061.00071	626 626 70	375 435	50	1	5.7
300061.00072	626 626 70	375 435	50	1	5.7
300061.00073	626 626 70	375 435	50	1	5.7
300061.00074	626 626 70	375 435	50	1	5.7
Type of equipment: EM 3h					
300061.00075B	626 626 70	375 435	50	1	6.7



Luminous flux tolerance +/- 10%.

Lighting beam, light intensity distribution and light efficiency were examined in accordance with the EN ISO 17025:2005 norm for EN13032 norm series and the LM-79 norm.
Up-to-date product info available on our website www.lugbox24.com

Code	Dimensions [mm] L W H	Mounting dimensions [mm] L W	Pallet quantity	Quantity in package	Net weight [kg]
Type of equipment: EM 3h					
300061.00076B	626 626 70	375 435	50	1	6.7
300061.00077B	626 626 70	375 435	50	1	6.7
300061.00078B	626 626 70	375 435	50	1	6.7


ACCESSORIES



150180.00700

Disassembly suction cup

LIGHT BEAM CURVES



Luminous flux tolerance +/- 10%.

Lighting beam, light intensity distribution and light efficiency were examined in accordance with the EN ISO 17025:2005 norm for EN13032 norm series and the LM-79 norm.

Up-to-date product info available on our website www.lugbox24.com